



Fig.1



型号 Type	图号 Fig.	尺寸 Dimenssions(mm)						有效参数 Effective Parameters				AL(±30%)				重量 Wt(g/set)
		A	B	C	D	E	F	C ₁ (mm ⁻¹)	Le(mm)	Ae(mm ²)	Ve(mm ³)	BH5.5	BH7	BH10	BH12	
SQ1212	1	12.5±0.4	12.0±0.4	4.4±0.3	3.5±0.4	8.9±0.4	5.0±0.4	2.33	46.17	19.83	915.55	/	/	/	4200	2.65
SQ1414	1	14.5±0.4	14.0±0.4	5.7±0.3	/	5.1±0.4	9.6±0.4	2.17	36.53	16.80	613.70	/	/	/	5800	4.00
SQ14.75	1	14.75±0.3	9.18±0.3	6.17±0.3	/	9.85±0.3	4.25±0.3	2.39	36.49	15.29	557.93	/	/	/	5500	2.85
SQ1515	1	15.2±0.4	15.2±0.4	5.1±0.3	4.7±0.3	11.0±0.4	5.9±0.4	2.65	39.36	14.87	585.28	/	/	/	5800	3.70
SQ1515/6.0	1	15.2±0.4	15.2±0.4	5.7±0.3	4.7±0.3	11.0±0.4	5.9±0.4	2.33	46.17	19.83	915.55	/	/	/	6000	4.60
SQ1816	1	17.8±0.4	16.2±0.4	5.5±0.3	/	13.0±0.4	6.0±0.4	1.69	33.73	19.98	673.93	/	/	/	6200	5.00
SQ1918	1	19.0±0.5	18.3±0.4	5.5±0.3	/	14.0±0.5	8.2±0.4	3.16	54.20	17.15	929.53	/	/	/	5400	5.30
SQ2018	1	20.0±0.5	18.1±0.5	5.9±0.3	/	15.1±0.5	8.2±0.4	2.52	55.15	21.92	1208.89	/	/	/	6000	6.40
SQ2118	1	21.0±0.4	18.1±0.4	5.8±0.3	/	14.6±0.4	8.2±0.4	2.82	56.80	20.12	1142.82	/	/	/	6500	7.00
SQ2318	1	22.8±0.5	18.1±0.5	5.0±0.3	/	14.8±0.5	9.1±0.4	2.62	58.59	22.34	1308.90	/	/	/	6000	7.20
SQ2418	1	24.0±0.5	17.5±0.4	6.0±0.3	/	20.0±0.3	6.5±0.4	2.89	53.18	18.43	980.11	/	/	/	6000	7.20
SQ2820	1	28.0±0.5	20.0±0.4	6.5±0.3	/	22.0±0.3	8.0±0.4	2.43	67.60	27.80	1879.28	/	/	/	6300	10.40
SQ3122	1	31.1±0.5	22.3±0.4	8.5±0.3	/	22.1±0.3	6.3±0.4	1.35	72.42	53.69	3888.23	/	/	/	7500	16.50
SQ3128	1	28.8±0.5	31.0±0.4	11.1±0.3	/	16.8±0.3	10.0±0.4	0.84	75.00	89.60	6720.00	/	/	/	10000	31.50
SQ3324	1	33.4±0.5	24.0±0.4	8.0±0.3	/	23.0±0.4	10.0±0.4	1.54	83.24	54.01	4495.79	5000	/	/	/	25.50

注:AL值测试条件:1KHz、0.3V。(Remark:Testing conditon for AL:1KHz、0.3V.)

以上为本公司标准规格, 可根据客户特殊要求进行设计。(The above is the usually type, we can redesign according to costomer's request.)