







CP型功率铁氧体产品系列

     															
<p>Fig.1                      Fig.2                      Fig.3                      Fig.4                      Fig.5                      Fig.6</p>															
规格Type	图形Fig	尺寸Dimensions(mm)											电感L(uH)	Q	重量(克/付)
		A	A1	B	C	C1	C2	D	D1	D2	F	G			
CP47*2.4	1	47.0±0.4	45±0.4	2.4±0.1	13.10Ref	11.66±0.3	10.80Ref	3.2±0.15	2±0.15	3.0Ref	1±0.15	0.85Ref	6.30±8%	135±25%	21.80
CP49*0.85	2	49.0±0.5	/	0.85±0.05	9.89±0.2	/	/	2.5±0.2	1.875±0.125	5.26±0.2	/	/	/	/	13.60
CP49*1.15	2	49.0±0.5	/	1.15±0.05	9.89±0.2	/	/	2.5±0.2	1.875±0.125	5.26±0.2	/	/	/	/	17.00
CP49*22	2	49.0±0.5	/	21±0.5	9.89±0.2	/	/	2.5±0.2	1.875±0.125	5.26±0.2	/	/	/	/	17.00
CP50*1.0	3	49.5±0.5	/	1±0.1	/	/	/	/	/	/	/	/	/	/	14.00
CP50*30.0	3	49.5±0.5	/	30±0.5	/	/	/	/	/	/	/	/	/	/	14.00
CP50*5.3*1.0	4	49.5±0.5	/	1±0.1	5.3±0.3	/	/	/	/	/	/	/	/	/	14.00
CP50*5.3*30.0	4	49.5±0.5	/	30±0.5	5.3±0.3	/	/	/	/	/	/	/	/	/	14.00
CP52*47*0.8	5	51.5±0.5	/	0.8±0.1	46.5±0.5	/	/	43.4±0.5	/	/	/	/	/	/	11.50
CP52*47*30.0	5	51.5±0.5	/	30±0.5	46.5±0.5	/	/	43.4±0.5	/	/	/	/	/	/	11.50
CP50*48.5*5.3*30	6	49.5±0.5	48.5±0.5	30±0.5	5.3±0.3	4.95±0.3	2.9±0.3	14.7ref	2.9±0.3	2.7±0.3	/	7.5±0.3	/	/	14.00

注: AL值测试条件:1KHz、0.3V、100Ts。(Remark:Testing conditon for AL:1KHz、0.3V、100Ts.)

以上为本公司标准规格,可根据客户特殊要求进行设计。(The above is the usually type, we can redesign according to costomer's request.)