

I型功率铁氧体产品系列

Fig. 1	Fig. 2	Fig. 3	Fig. 4	Fig. 5				
规格Type	图形Fig	尺寸Dimensions(mm)			抗压强度 (N)	Q值	电感 L(uH)	重量(克/只)
		A	B	C	Strength (N)	Q	BP40/BP95	Wt(g/set)
I12.8×10.5×4.8	1	12.80±0.20	10.50±0.20	4.80±0.15	/	/	/	3.10
I14.5×10.4×4.8	1	14.50±0.30	10.20-10.50	4.80±0.15	/	/	/	3.45
I14.8×10.5×4.8	1	14.80+0/-0.30	10.50±0.20	4.85±0.15	/	/	/	3.60
I18*3*2.2	1	18.0±0.30	3.0±0.10	2.2±0.10	/	/	/	
I19.6*19*6	1	26.9±0.50	19.65±0.35	6.0±0.05	/	/	/	
I22×6×2.2	1	22.00±0.40	6.0±0.20	2.20±0.15	/	/	/	1.45
I22×16×6.0	1	22.00±0.40	16.0±0.20	6.00±0.15	/	/	/	10.5
I22×18.2×6.0	1	22.00±0.30	18.2+0.40	6.00±0.10	/	/	/	13.00
I30*18*4	1	30.00±0.50	18.0±0.10	4.00±0.10	/	/	/	
I32×12×4.0	1	36.00±0.30	12.0±0.20	4.00±0.10	/	/	/	8.70
I23×22×6.0	1	23.00±0.30	22.0±0.30	6.00±0.10	/	/	/	16.00
I36×32×12	1	36.00±0.30	32.0±0.30	12+0.1/-0.3	/	/	/	71.00
I40×15×3.5	1	40.00±0.40	15.0±0.25	3.50±0.10	/	/	/	12.00
I40×15×5.0	1	40.00±0.40	15.0±0.25	5.00±0.10	/	/	/	14.40
I40×40×15	1	40.00±0.40	40.0±0.40	14.80±0.20	/	/	/	121.90
I155×68×12	1	155.5±0.50	68.00±0.50	12.0±0.20	/	/	/	
I195.5×68×18	1	195.5±0.50	68.00±0.50	18.0±0.20	/	/	/	
I55×20×5	2	54.80±0.40	19.85±0.20	4.90±0.15	≥160	≥1.53	≥625	24.90
I96.4×20×7.7	2	96.40±0.50	20.00±0.20	7.50±0.20	≥200	/	/	70.00
I22×15×5.0	3	22.00±0.30	15.0±0.20	5.00±0.15	/	/	> 280	8.00
I26×15×5.0	3	26.00±0.35	15.0±0.20	5.00±0.15	/	/	> 310	9.45

I26.8*19.5*5								
I29×15×5.0	3	29.00±0.35	15.0±0.25	5.00±0.15	/	/	> 340	10.50
I33×18×4.5	3	33.00±0.50	18.0±0.30	4.50±0.20	≥160	≥0.8	≥370	13.10
I35×15×5	3	35.00±0.30	15.0±0.20	5.00±0.20	/	/	/	12.60
I40×15×5.0	3	40.00±0.30	15.0±0.20	5.00±0.20	/	/	/	14.50
I40×36×4.5	3	40.00±0.50	36.0±0.50	4.50±0.20	/	/	/	30.60
I45×12×5	3	45.00±0.50	11.80±0.20	5.00±0.20	≥160	/	/	13.20
I47×14×5	3	47.00±0.50	14.00±0.20	5.00±0.20	≥160	≥1.25	≥500	15.30
I49.6×10×2.5	3	49.60±0.40	10.00±0.15	2.50±0.10	≥55	/	/	7.50
I50×15×5	3	50.0±0.50	14.90±0.15	4.85±0.15	≥160	≥1.10	≥510	17.25
I50×18×4.5	3	50.0±0.50	18.0±0.30	4.50±0.20	≥160	/	/	19.50
I55×7.3×3.5	3	55.0±0.45	7.30±0.20	3.50±0.20	/	/	/	6.80
I55×8×5	3	55.0±0.50	8.0±0.15	5.0±0.15	≥160	≥1.25	≥480	10.70
I55×15×5	3	54.85±0.40	14.90±0.20	4.90±0.15	≥160	≥1.3	≥545	19.00
I55×18×4.5	3	55.00±0.40	18.00±0.30	4.50±0.20	≥160	≥1.4	≥575	20.60
I60×14×5	3	60.00±0.50	14.00±0.20	5.00±0.20	≥160	≥1.55	≥605	20.00
I60×15×5	3	59.50±0.50	14.90±0.20	4.90±0.10	≥160	≥1.35	≥575	21.10
I60×14.6×4.6	3	60.00±0.50	14.50±0.25	4.60±0.20	≥160	/	/	18.65
I63×12×4.8	3	63.00±0.70	12.00±0.20	4.80±0.15	≥160	≥1.35	≥570	17.10
I65*15*5	3	65.00±0.60	15.00±0.30	5.00±0.20	≥160	/	/	23.65
I67×18×4.5	3	67.00±0.50	18.00±0.30	4.50±0.20	≥160	≥1.60	≥670	26.10
I70×15×5	3	70.00±0.50	14.90±0.20	5.00±0.20	≥160	≥1.60	≥660	24.80
I70×70×30	3	70.00±0.70	70.00±0.70	30.00±0.5	/	/	/	751.00
I75*15*5	3	75.00±0.70	15.00±0.30	5.00±0.20	≥160	/	/	26.80
I80×40×1.2	3	80.00±0.50	40.0±0.50	1.20±0.10	/	/	/	38.20
I84.2×15×5	3	84.20±0.80	14.90-0.50	5.00-0.30	≥160	/	/	29.30
I84.5×15×5	3	84.50±0.50	14.90±0.20	5.00±0.20	≥160	/	/	30.60
I84.7×18×4	3	84.70-0.30	18.00-0.25	4+0.1/-0.15	≥100	/	/	37.20
I85.5×18×4	3	85.50±0.75	18.60±0.20	4.65±0.20	≥120	/	/	39.60
I86×15×5	3	86.00±0.85	14.90-0.50	5.00-0.30	≥160	/	/	29.90
I90×15×5	3	90.00±0.50	15.0±0.30	5.0±0.20	≥160	≥2.0	≥800	32.35
I90×8×4	3	89.90±0.40	7.90±0.10	3.90±0.10	≥55	/	/	15.30
I94×50×15	3	94+0.2/-0.6	50.0±0.30	15.0±0.30	/	/	/	381.00

I49×29.5×7.5	4	49.00±0.50	29.50±0.4	7.50±0.20	/	/	/	51.00
I50×50×9.7	4	50.0±0.30	50.0±0.30	9.70±0.20	/	/	/	
I23×6×2.2	5	23.00±0.30	6.0±0.15	2.20±0.05	/	/	/	1.70

注: 1. AL值测试条件:1KHz、 0.3V、 100Ts。(Remark:Testing conditon for AL:1KHz、 0.3V、 100Ts.)

2.Q值测试条件:1KHz、 1V、 100Ts。(Q:Testing conditon for AL:1KHz、 1V、 100Ts.)

3.抗压强度测试条件: 测试间距40mm, 测试速度: 30mm/mim.

以上为本公司标准规格, 可根据客户特殊要求进行设计。(The above is the usually type, we can redesign according to costomer's request.)